

Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX

info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No.

LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

## ORDER CONFIRMATION

Not Rated Yet

### Sales price 1249,00 €

Salesprice with discount Incl. VAT 21%: 216,77 €





## Description

Ready to hunt like a pro? Look no further than the Mars LTV thermal riflescope from ATN. Packed with features and super affordable, the Mars LTV is one of the lightest and easiest-to-use thermal scopes on the market. Incorporating video recording capability, the Mars LTV features the latest in advanced 12-micron thermal sensors, a 60 Hz refresh rate, a long-lasting rechargeable battery, and user-friendly controls. Built for tough conditions, the Mars LTV is available in multiple lenses and sensor resolutions to fit nearly any budget. Mounting is easy with standard 30 mm rings. The Mars LTV system is highly-versatile and can be used with a variety of platforms. Get accuracy, optimal image quality, and convenience that won't break the bank: equip your favorite weapon with an ATN Mars LTV and see the difference.

Features:

- ONE SHOT ZERO
- STEP ZOOM
- RECORD VIDEO
- 3D ACCELEROMETER
- MULTIPLE RETICLES
- USB TYPE C

Page 1/2

Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

# • ULTRA LOW POWER CONSUMPTION

- ERGONOMIC DESIGN
- LIGHT WEIGHT

## Included in the set:

- Eyecup
- Scope cover
- USB-C cable
- Lens tissue

Mounting an using the scope:

One shot zeroing feature:

Recording sample MARS LTV 320x240:

Specifications for all versions of Mars LTV thermal riflescope:

	Mars LTV 160		Mars LTV 320			Mars LTV 640			
Item #	MSLTV112X	MSLTV119X	MSLTV319X	MSLTV325X	MSLTV335X	MSLTV625X	MSLTV635X	MSLTV650X	
Resolution	160x120	ox / 12 μm	320x240 px / 12 μm			640x480 / 12 μm			
Magnification	3-9x	5–15x	3-9x	4–12x	5–15x	2-6x	3-9x	4–12x	
Field of view	8.7°x6.5°	6.2°x4.7°	11.6°x8.7°	8.8°x6.6°	6.3°x4.7°	17.6°x13.2°	12.6°x9.4°	8.8°x6.6°	
Display Resolution	1280x720 px								
Eye relief	90 mm								
Video Record Resolution	Up to 1280×720 px								
3D Accelerometer	Yes								
Color modes	White Hot/ Black Hot/Color Modes								
Reticles	Multiple Patterns								
Micro SD card	4 to 64 GB								
USB, type C	Yes								
Mount	30 mm Standard Rings (not included)								
Internal Lithium Ion Battery	9 + hrs								
IP rating	Weather resistant								
<b>Human Detection Range</b>	475 y/m	625 y/m	715 y/m	910 y/m	1510 y/m	740 y/m	920 y/m	1670 y/m	
Human Recognition Range	240 y/m	315 y/m	305 y/m	455 y/m	680 y/m	375 y/m	485 y/m	700 y/m	
<b>Human Identification Range</b>	160 y/m	210 y/m	200 y/m	290 y/m	400 y/m	250 y/m	325 y/m	440 y/m	
Dimensions	292x56x55 mm / 11.5" x 2.2" x 2.2"								
Weight		1.4 lb/ 650 g							
Warranty		3 years							

Page 2/2