

Online store WWW.LYNXGEAR.LV Company: SIA LATLYNX

info@lynxgear.lv, +371 26159668 Reg. No. 45403038162, VAT Reg. No.

LV45403038162,

Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet



Sales price 369,00 €

Salesprice with discount Incl. VAT 21%: 64,04 €

KHS Seeker with black NATO band



Description

Uncompromising equipment - uncompromising design.

The KHS Seeker impresses not only with its high-quality features, such as a SWISS MADE quartz movement, a scratch-resistant sapphire crystal, and the robust stainless steel case, but also with its high visual appeal. The straight-lined design given to all Seeker variants is also refined in the silver-colored variants by a fine cut on the dial and the elegant alternation of brushed and polished surfaces. KHS Seeker - Straight to the target.

• Case

Stainless steel case, black IP-coated, screwed stainless steel caseback, black IP-coated, screwed crown, black IP-coated.

Watch Glass

Scratch resistant sapphire crystal.


• Water resistance

10 bar.

This watch is tested for water resistance up to 10 bar, which corresponds to the pressure of an assumed water column of 100 meters. Thus, this watch is suitable for e.g. bathing, showering, hand washing, frequent swimming, snorkeling and diving.

• Dial and hands

Page 1/2



Legal address: Baznīcas iela 8, Aizkraukle, Aizkraukles novads, LV-5101, LATVIJA

Bank Account: LV87UNLA0050021387494 AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Black dial with Arabic numerals and date window, 3 hands (hour, minute and second), second hand with C1 luminous color for tactically accurate operations.

Movement

Quartz movement, SWISS MADE, 3 hands, date display.

Hour, minute, center second, stop-second with crown pulled, date with date quickset, very easy to use.

Features

Longer battery life due to low power consumption, additional energy saving function when crown is pulled out: reduction of power consumption by approx. 70%, EOL indicator (battery "End Of Life" indicator = second hand jumps forward several seconds) for timely indication of a soon exhausted battery, battery no. 371, magnetic field shielding 18.8 Oe, shock resistance NIHS 91-10, operating temperature 0-50 °C.

Illumination

C1 Luminous paint

• Dimensions

 $56,00 \text{ mm} \times 50,00 \text{ mm} \times 12,5 \text{ mm} \text{ (L } \times \text{W } \times \text{H)}.$

Weight

0,092 kg.

Brand country - Germany

Page 2/2