



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet

Sales price 805,00 €

Salesprice with discount

Incl. VAT 21%: 139,71 €



| | |
|------------------------------------|-------------------------------------|
| Interior Dimensions (L×W×D) | 71.6 × 50.2 × 44.8 cm |
| Exterior Dimensions (L×W×D) | 80 × 58.1 × 48.3 cm |
| Lid Depth | 8.9 cm |
| Bottom Depth | 35.9 cm |
| Total Depth | 44.8 cm |
| Interior Volume | 0.161 m ³ |
| Padlock Hole Diameter | 8 mm |
| Weight (with foam) | 19.1 kg |
| Weight (empty) | 15.5 kg |
| Buoyancy | 159 kg |
| Body Material | Polypropylene |
| Latch Material | ABS |
| Hardware | Stainless steel |
| Foam Material | 1.3 lb Polyurethane |
| Purge Valve | Automatic with 3-micron hydrophobic |



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

| | |
|-------------------|--|
| | vent |
| Temperature Range | -40 °C to +88 °C |
| Wheels | 4 polyurethane with stainless bearings |
| Extendable Handle | Yes |
| Certifications | IP67 / DEF STAN 81-41 / MIL-STD 810G (Fungus test) |

Downloads

- [DEF STAN 81-41 Certification \(PDF\)](#)
- [1660 IP67 Certification \(PDF\)](#)
- [MIL-STD 810G Fungus Resistance Test \(PDF\)](#)

Why Choose the PELI 1660EU Protector Case?

- **Unmatched protection:** Watertight, dustproof, crushproof - engineered for the toughest conditions
- **Military-grade certification:** IP67 and DEF STAN 81-41 compliant for professional and defense applications
- **Versatile mobility:** Four durable wheels and a retractable handle for effortless transport
- **Customizable interior:** Includes Pick N Pluck™ foam for personalized fit and equipment safety
- **Temperature resistant:** Performs from -40°C to +88°C

Glossary

- **IP67:** International protection rating ensuring dust-tightness and submersion resistance up to 1 meter for 30 minutes.
- **DEF STAN 81-41:** British military standard for robust, shock-resistant protective cases.
- **Pick N Pluck™ Foam:** Pre-scored foam that allows easy customization to fit specific equipment shapes.
- **Automatic Pressure Valve:** Equalizes internal air pressure to prevent vacuum lock during altitude or temperature changes.

Manufacturer

Peli Products, S.L.U. (EU Representative of Peli, USA)

c/ Provença, 388, Planta 7

08025 Barcelona, Spain

Phone: +34 934 674 999

Email: This email address is being protected from spambots. You need JavaScript enabled to view it.



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

```
document.getElementById('cloak5849aacdc99b0f4978466ee075077315e').innerHTML  
= ''; var prefix = 'ma' + 'il' + 'to'; var path = 'hr' + 'ef' + '='; var  
addy5849aacdc99b0f4978466ee075077315e = 'info' + '@';  
addy5849aacdc99b0f4978466ee075077315e = addy5849aacdc99b0f4978466ee075077315e  
+ 'peli' + '.' + 'com'; var addy_text5849aacdc99b0f4978466ee075077315e =  
'info' + '@' + 'peli' + '.' + 'com';document.getElementById('cloak5849aacdc9  
9b0f4978466ee075077315e').innerHTML +=  
'+addy\_text5849aacdc99b0f4978466ee075077315e+';  
Website: www.peli.com
```

© Peli Products, S.L.U. / Peli USA. Specifications may change without notice for
product improvement.