



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet

Sales price 972,00 €

Salesprice with discount

Incl. VAT 21%: 168,69 €



Interior: 104.4 × 54.7 × 37.8
cm

1-4 Weeks



Description

Sensitive equipment needs protection, and since 1976 the answer has been the Peli™ Protector Case. These cases are designed rugged, and travel the harshest environments on earth. Against the extreme cold of the artic or the heat of battle, Peli cases have survived.

Made in the USA, these tough cases are designed with an automatic purge valve, that equalizes air pressure, a watertight silicone O-ring lid, over-molded rubber handles and stainless steel hardware.

- 4 strong polyurethane wheels with stainless steel bearings
- The new class of XXL Peli Transport Cases
- Watertight, crushproof, and dustproof
- 50/50 lid-to-base ratio for easy loading
- Automatic Pressure Equalization Valve - balances interior pressure, keeps water out
- Completely detachable lid for full access
- Easy open Double Throw latches
- Fold down handles
- O-ring seal
- Open cell core with solid wall design - strong, light weight
- Stainless steel padlock protectors

Specs:



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznicas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

- INTERIOR (L X W X D) 41.12" x 21.54" x 14.88" (104.4 x 54.7 x 37.8 cm)
- EXTERIOR (L X W X D) 44.90" x 25.32" x 16.50" (114 x 64.3 x 41.9 cm)
- LID DEPTH: 7.58" (19.3 cm)
- BOTTOM DEPTH: 7.30" (18.5 cm)
- TOTAL DEPTH: 14.88" (37.8 cm)
- INT VOLUME: 7.63 ft³ (0.216 m³)
- WEIGHT WITH FOAM: 49.00 lbs (22.2 kg)
- WEIGHT EMPTY: 38.40 lbs (17.4 kg)
- BUOYANCY: 500.00 lbs (226.8 kg)
- FOAM LAYERS: Layer 1 (Lid): 4 cm - Pad / Layer 2 (Base): 3.3 cm - Pad / Layer 3 (Base): 7.6 cm - Diced Lid / Layer 4 (Base): 7.6 cm - Diced Lid / Layer 5 (Base): 7.6 cm - Diced Base / Layer 6 (Base): 7.6 cm - Diced Base
- BODY: Polypropylene
- LATCH: EXL
- O-RING: Polymer
- PINS: Stainless Steel
- FOAM: 1.3 lb Polyurethane
- PURGE BODY: ABS
- PURGE VENT: 3 Micron Hydrophobic Non-Woven
- MINIMUM TEMPERATURE: -40° F (-40 ° C)
- MAXIMUM TEMPERATURE: 210° F (99 ° C)
- WHEELS: 4

Certifications

STANAG 4280 / Def Stan 81-41