



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznīcas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

Not Rated Yet



Sales price 29,95 €

Salesprice with discount

Incl. VAT 21%: 5,20 €



Description

Highly effective, fast and easy to use cleaner for suppressors of all types, materials and coatings. No more laborious cleaning procedures due to self-active cleaning formula that makes short work of stubborn fouling. Modern suppressors combine several advantages: Noise suppression, recoil reduction and precision enhancement. But as the degree of accumulated fouling increases, the performance of the suppressor drops substantially. Therefore, suppressor cleaning should not be disregarded and the suppressor be cleaned regularly. If no manufacturer's recommendation exists, suppressors should be cleaned, at least, when heavily soiled or when they have not been in use over a longer period of time to prevent the formation of acidic condensates.

Suppressor Cleaner Evolution has been developed in collaboration with the world's leading manufacturer of suppressors for the military and the authorities, Swiss B&T AG based in Thun. SchleTek Evolution is easy to use and rapid acting. It cleans all types of suppressors with its special self-active cleaning formula and removes even stubborn fouling. Laborious cleaning procedures are now a thing of the past.

Even suppressors which cannot be disassembled, carbon suppressors and suppressors with rows of holes or super-fine suppression maximising baffles, which are usually very difficult to clean, can be cleaned easily and effortless with SchleTek Evolution. The suppressor has to be closed on



Online store WWW.LYNXGEAR.LV
Company: SIA LATLYNX
info@lynxgear.lv, +371 26159668
Reg. No. 45403038162, VAT Reg. No.
LV45403038162,
Legal address: Baznīcas iela 8,
Aizkraukle, Aizkraukles novads,
LV-5101, LATVIJA
Bank Account: LV87UNLA0050021387494
AS SEB Bank, SWIFT: UNLALV2X

ORDER CONFIRMATION

one end, and then filled with the cleaner from the opposite end. Suppressors which can be taken apart are simply put into a container filled with SchleTek Evolution. After a reaction time of only 20 to 30 minutes, for stubborn fouling up to a maximum of 120 minutes, all residue can be easily flushed out or rinsed off with warm water. Heating to approximately 50°C (122°F) additionally increases cleaning efficiency. SchleTek Evolution is also suitable for ultrasonic baths. SchleTek Suppressor Cleaner Evolution is environmentally friendly, water soluble, and has been positively tested for compatibility of materials. Due to its special pH-neutral formula it does not harm any surfaces and is suitable for all materials and coatings, including Cerakote™. To protect and preserve suppressors, spray SchleTek 2in1 Gun-Tuning on thread and suppressor after cleaning and fully drying. Available in 500 ml bottle, 1 litre bottle, and 5 litre canister. Additional sizes available on request.

Made in Germany.